

ARTIFACT SHEET

Enter artifact number below. Artifact number is application number + artifact type code (see list below) + sequential letter (A, B, C . . .). The first artifact folder for an artifact type receives the letter A, the second B, etc..
Examples: 59123456PA, 59123456PB, 59123456ZA, 59123456ZB

09871313BA
Indicate quantity of a single type of artifact received but not scanned. Create individual artifact folder/box and artifact number for each Artifact Type.

☐

CD(s) containing:

computer program listing

Doc Code: Computer

pages of specification

and/or sequence listing

and/or table

Doc Code: Artifact

content unspecified or combined

Doc Code: Artifact

☐

Artifact Type Code: P

☐

Artifact Type Code: S

☐

Artifact Type Code: U

☐

Stapled Set(s) Color Documents or B/W Photographs

Doc Code: Artifact Artifact Type Code: C

☐

Microfilm(s)

Doc Code: Artifact Artifact Type Code: F

☐

Video tape(s)

Doc Code: Artifact Artifact Type Code: V

☐

Model(s)

Doc Code: Artifact Artifact Type Code: M

☒

Bound Document(s)

Doc Code: Artifact Artifact Type Code: B

☐

Confidential Information Disclosure Statement or Other Documents
marked Proprietary, Trade Secrets, Subject to Protective Order,
Material Submitted under MPEP 724.02, etc.

Doc Code: Artifact Artifact Type Code X

☐

Other, description: _____

Doc Code: Artifact Artifact Type Code: Z

The
United
States
of
America



The Commissioner of
Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

J. Todd Ichni

Acting Commissioner of Patents and Trademarks

Attest *Mary A. Dean*

United States Patent [19]

Perino et al.

[11] Patent Number: 5,908,333
 [45] Date of Patent: Jun. 1, 1999

33

[54] CONNECTOR WITH INTEGRAL
TRANSMISSION LINE BUS

[75] Inventors: Donald Victor Perino, Los Altos;
James Anthony Gasbarro, Mountain
View; John Bradly Dillon, deceased,
late of Palo Alto, all of Calif., Nancy
David Dillon, legal representative

[73] Assignee: Rambus, Inc., Mt. View, Calif.

[21] Appl. No.: 08/897,788

[22] Filed: Jul. 21, 1997

[51] Int. Cl.⁶ H01R 9/09
 [52] U.S. Cl. 439/631; 361/775; 174/72 B
 [58] Field of Search 439/61, 631; 361/785,
361/775, 788; 172/71 B, 72 B, 88 B

[56] References Cited

U.S. PATENT DOCUMENTS

2,904,768	9/1959	Rasmussen	439/631
3,085,177	4/1963	Thompson	439/593
3,368,117	2/1968	Pond et al.	361/775
3,399,372	8/1968	Uberbacher	439/60
3,567,999	3/1971	Larson et al.	361/775
4,241,381	12/1980	Cobaugh et al.	439/61
4,536,826	8/1985	Ahiskali	361/775
4,616,893	10/1986	Feldman	439/83

4,867,696	9/1989	Demler, Jr. et al.	174/72 B
5,104,324	4/1992	Grabbe et al.	439/62
5,329,424	7/1994	Patel	361/775

Primary Examiner—Neil Abrams
 Attorney, Agent, or Firm—Blakely Sokoloff Taylor &
 Zafman LLP

[57]

ABSTRACT

A socket (14) includes a first bus conductor (22a) having two or more contact regions (24) and a second bus conductor (22b) arranged substantially parallel to the first bus conductor and having two or more contact regions (24). The first and second bus conductors are spaced relative to one another so as to provide a predetermined electrical impedance and may be arranged to carry electrical signals as transmission lines. A dielectric spacer (36) may be disposed between the first and second bus conductors to provide the spacing. Contact regions (24) of the first and second conductors (22a, 22b) may provide compliant coupling regions for the socket (14). The contact regions (24) of the first bus conductor (22a) may be positioned within the socket (14) so as to contact a lead disposed on a first side of a circuit element (16) and the contact regions (24) of the second bus conductor (22b) may be positioned within the socket (14) so as to contact the lead disposed on the second side of the circuit element (16).

17 Claims, 11 Drawing Sheets

